

# TERRAIN TAMER E-LOCKER FITTING GUIDE – 2024.

| VEHICLE MAKE & MODEL                     | YEAR         | F/R   | SUSP | SPLINE | ELOCKER PART # | BEARING KIT PART# | CROWN WHEEL TORQUE | BEARING CAP TORQUE | BACK LASH                | COMMENTS                                                                                        | TT DIFF LOCKER KIT |
|------------------------------------------|--------------|-------|------|--------|----------------|-------------------|--------------------|--------------------|--------------------------|-------------------------------------------------------------------------------------------------|--------------------|
| <b>TOYOTA</b>                            |              |       |      |        |                |                   |                    |                    |                          |                                                                                                 |                    |
| <b>LANDCRUISER</b>                       |              |       |      |        |                |                   |                    |                    |                          |                                                                                                 |                    |
| 40 SERIES                                | 1969-1984    | FRONT | Live | 30     | A9378          | TTEL01            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") | Early models will require upgrade to 50mm bearing                                               | A9378-1TT          |
|                                          |              | REAR  | Live | 30     | A9378          | TTEL01            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") | Early models will require upgrade to 50mm bearing not suited to c-clip diff                     | A9378-1TT          |
| 60 SERIES                                | 1980-1990    | FRONT | Live | 30     | A9378          | TTEL01            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") |                                                                                                 | A9378-1TT          |
|                                          |              | REAR  | Live | 30     | A9378          | TTEL01            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") |                                                                                                 | A9378-1TT          |
| LJ70, RJ70                               | 1984-        | FRONT | Live | 30     | A9334          | TTEL07            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-7TT          |
|                                          |              | REAR  | Live | 30     | A9334          | TTEL05            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-5TT          |
| 70,71,73,74,75 SERIES                    | 1984-1990    | FRONT | Live | 30     | A9378          | TTEL01            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") |                                                                                                 | A9378-1TT          |
|                                          |              | REAR  | Live | 30     | A9378          | TTEL01            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") |                                                                                                 | A9378-1TT          |
| 70, 73, 75 SERIES                        | 1990-1999    | FRONT | Live | 30     | A9334          | TTEL02            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-2TT          |
|                                          |              | REAR  | Live | 30     | A9378          | TTEL03            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") |                                                                                                 | A9378-3TT          |
| 76, 78 79 SERIES                         | 1999-Current | FRONT | Live | 30     | A9334          | TTEL02            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-2TT          |
|                                          |              | REAR  | Live | 30     | A9574          | TTEL04            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9574-4TT          |
| 80 SERIES                                | 1990-1998    | FRONT | Live | 30     | A9334          | TTEL02            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-2TT          |
|                                          |              | REAR  | Live | 30     | A9378          | TTEL03            | 120Nm (89ftlb)     | 110Nm (81ftlb)     | 0.15-0.20mm (.006-.008") |                                                                                                 | A9378-3TT          |
| 100 SERIES                               | 1998-2006    | FRONT | Ind. | 30     | A10976         | TTEL12            | 96Nm (71ftlb)      | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007") |                                                                                                 | A10976-12TT        |
|                                          |              | REAR  | Live | 32     | A9574          | TTEL04            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9574-4TT          |
| 105 SERIES                               | 1998-2006    | FRONT | Live | 30     | A9334          | TTEL02            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-2TT          |
|                                          |              | REAR  | Live | 32     | A9574          | TTEL04            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9574-4TT          |
| 200 SERIES                               | 2007-2021    | FRONT | Ind. | 34     | A11092         | TTEL13            | 135Nm (100ftlb)    |                    | 0.15-0.25mm (.006-.010") |                                                                                                 | A11092-13TT        |
|                                          |              | REAR  | Live | 32     | A9574          | TTEL04            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9574-4TT          |
| 300 SERIES                               | 2022 -       | FRONT | Ind. | 36     | A15729         | TTEL30            |                    |                    |                          | Suits non factory diff lock                                                                     | A15729-30TT        |
|                                          |              | REAR  | Live | 32     | A15736         | TTEL31            |                    |                    |                          | Suits non factory diff lock                                                                     | A15736-31TT        |
| <b>LANDCRUISER / PRADO</b>               |              |       |      |        |                |                   |                    |                    |                          |                                                                                                 |                    |
| 90 SERIES                                | 1996-2002    | FRONT | Ind. | 27     | A11167         | TTEL06            | 96Nm (71ftlb)      | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007") | Some light grinding may be required to clear electromagnet                                      | A11167-6TT         |
|                                          |              | REAR  | Live | 30     | A9334          | TTEL14            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-14TT         |
| 120 SERIES                               | 2002-2009    | FRONT | Ind. | 30     | A10994         | TTEL09            | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | 3.73 & Down ratio may require grinding in housing to seat electromagnet                         | A10994-9TT         |
|                                          |              |       |      |        | A11110         |                   | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | 3.93 & Up ratio may require grinding in housing to seat electromagnet                           | A11110-9TT         |
|                                          |              | REAR  | Live | 30     | A9334          | TTEL14            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-14TT         |
| 150 SERIES                               | 2009-        | FRONT | Ind. | 30     | A11110         | TTEL09            | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | Ratio 3.91 & Up diesel may require grinding in housing to seat electromagnet                    | A11110-9TT         |
|                                          |              |       |      |        | A10994         |                   | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | Ratio 3.73 & Down petrol may require grinding in housing to seat electromagnet                  | A10994-9TT         |
|                                          |              | REAR  | Live | 30     | A11114         | TTEL17            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A11114-17TT        |
| <b>HILUX / SURF / 4RUNNER / FORTUNER</b> |              |       |      |        |                |                   |                    |                    |                          |                                                                                                 |                    |
|                                          | 2015-        | FRONT | Ind. | 30     | A10994         | TTEL32            | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | Ratio 3.73 & Down may require grinding in housing to seat electromagnet.                        | A10994-32TT        |
|                                          |              |       |      |        | A11110         |                   | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | Ratio 3.93 & Up may require grinding in housing to seat electromagnet.                          | A11110-32TT        |
|                                          |              | REAR  | Live | 32     | A14334         | TTEL26            |                    |                    |                          | Suits factory diff lock replacement                                                             | A14334-26TT        |
|                                          | 2005-2014    | FRONT | Ind. | 30     | A10994         | TTEL09            | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | Ratio 3.73 & Down may require grinding in housing to seat electromagnet suits clamshell housing | A10994-9TT         |
|                                          |              |       |      |        | A11110         |                   | 95Nm (70ftlb)      |                    | 0.15-0.25mm (.006-.010") | Ratio 3.91 & Up may require grinding in housing to seat electromagnet suits clamshell housing   | A11110-9TT         |
|                                          |              | REAR  | Live | 30     | A9334          | TTEL14            |                    |                    |                          | Late model vehicles require bearing upgrade from 45mm to 50mm                                   | A9334-14TT         |
|                                          |              |       |      |        | A13412         |                   |                    |                    |                          | Os model variant dana spicer shim adjusted housing                                              |                    |
|                                          | 1988-2005    | FRONT | Ind. | 27     | A11444         | TTEL06            |                    |                    |                          | Suits 33mm output shaft or manual locking hub suits non clamshell housing                       | A11444-6TT         |
|                                          |              |       |      |        | A11412         |                   | 96Nm (71ftlb)      |                    | 0.13-0.18mm (.005-.007") | Suits non clamshell housing                                                                     | A11412-6TT         |
|                                          |              |       |      |        | A11167         |                   | 96Nm (71ftlb)      |                    | 0.13-0.18mm (.005-.007") | Suits clamshell housing                                                                         | A11167-6TT         |
|                                          |              | REAR  | Live | 30     | A9334          | TTEL05            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") | 80mm od hemisphere bearing                                                                      | A9334-5TT          |
|                                          |              | REAR  | Live | 30     | A9334          | TTEL14            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") | 83mm od hemisphere bearing                                                                      | A9334-14TT         |
|                                          | 1981-1997    | FRONT | Live | 30     | A9334          | TTEL07            | 95Nm (70ftlb)      | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010") |                                                                                                 | A9334-7TT          |

# TERRAIN TAMER E-LOCKER FITTING GUIDE – 2024.

| VEHICLE MAKE & MODEL    | YEAR      | F/R   | SUSP | SPLINE | ELOCKER PART # | BEARING KIT PART# | CROWN WHEEL TORQUE                                  | BEARING CAP TORQUE | BACK LASH                     | COMMENTS                                                                                                     | TT DIFF LOCKER KIT |
|-------------------------|-----------|-------|------|--------|----------------|-------------------|-----------------------------------------------------|--------------------|-------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------|
|                         |           | REAR  | Live | 30     | A9334          | TTEL05            | 95Nm (70ftlb)                                       | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010")      |                                                                                                              | A9334-5TT          |
| HIACE                   |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
| H100 / H200             | 1989-2016 | REAR  | Live | 30     | A9334          | TTEL14            | 95Nm (70ftlb)                                       | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010")      | Suits 10 bolt crown wheel diameter 8" will not replace oe diff lock                                          | A9334-14TT         |
| FJ CRUISER              |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
| GSJ15                   | 2005-2016 | FRONT | Ind. | 30     | A10994         | TTEL09            | 95Nm (70ftlb)                                       |                    | 0.15-0.25mm (.006-.010")      | Ratio 3.73 & Down may require grinding in housing to seat electromagnet will not suit models with oem locker | A10994-9TT         |
|                         |           |       |      |        | A11110         | TTEL09            | 95Nm (70ftlb)                                       |                    | 0.15-0.25mm (.006-.010")      | Ratio 3.91 & Up may require grinding in housing to seat electromagnet will not suit models with oem locker   | A11110-9TT         |
|                         |           | REAR  | Live | 30     | A11114         | TTEL14            | 95Nm (70ftlb)                                       | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010")      | Suits 10 bolt crown wheel will not suit models with oem locker                                               |                    |
| TACOMA USA              |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
|                         | 1995-2004 | FRONT | IFS  | 27     | A11167         | TTEL14            | 96Nm (71ftlb)                                       | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007")      | Suits clamshell housing                                                                                      | A11167-14TT        |
|                         |           | REAR  | Live |        | A13457         | TTEL15            | 96Nm (71ftlb)                                       | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007")      |                                                                                                              | A13457-15TT        |
|                         | 2005-     | FRONT | IFS  | 30     | A10994         | TTEL15            | 95Nm (70ftlb)                                       |                    | 0.15-0.25mm (.006-.010")      | Ratio 3.73 & Down housing may require grinding to seat electro magnet                                        | A10994-15TT        |
|                         |           |       |      | 30     | A11110         | TTEL16            | 95Nm (70ftlb)                                       |                    | 0.15-0.25mm (.006-.010")      | Ratio 3.93 & Up housing may require grinding to seat electro magnet                                          | A11110-16TT        |
|                         | 1995-2015 | REAR  | Live | 30     | A13457         | TTEL17            | 96Nm (71ftlb)                                       | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007")      |                                                                                                              | A13457-17TT        |
|                         | 2016-     | REAR  | Live | 30     | A9334          | TTEL14            | 95Nm (70ftlb)                                       | 95Nm (70ftlb)      | 0.15-0.25mm (.006-.010")      | 8" Crownwheel suits all autos excluding oe facrory locked vehicles                                           | A9334-14TT         |
| SEQUOIA, T-100 & TUNDRA |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
|                         | 1993-1998 | FRONT | IFS  | 27     | A11412         |                   | 96Nm (71ftlb)                                       |                    | 0.13-0.18mm (.005-.007")      | Suits non clamshell type housing                                                                             |                    |
|                         | 1999-2006 |       |      |        | A11167         |                   | 96Nm (71ftlb)                                       | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007")      | Suits clamshell type housing                                                                                 |                    |
|                         | 2007 -    | FRONT | IFS  | 34     | A11092         | TTEL13            | 135Nm (100ftlb)                                     |                    | 0.15-0.25mm (.006-.010")      |                                                                                                              | A11092-13TT        |
|                         | 1993-2006 | REAR  | Live | 30     | A13457         |                   | 96Nm (71ftlb)                                       | 85Nm (63ftlb)      | 0.13-0.18mm (.005-.007")      |                                                                                                              |                    |
|                         | 2007-     | REAR  | Live | 30     | A13971         |                   |                                                     |                    |                               | 10.5" Crownwheel                                                                                             |                    |
| <b>NISSAN</b>           |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
| PATROL                  |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
| GQ Y60 - GU Y61         | 1988-2016 | FRONT | Live | 31     | A9684          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)      | 0.15-0.20mm (.006-.008")      | Ttel10 will be required to suit 50mm bearing journal up-grade                                                | A9684-10TT         |
|                         |           | REAR  | Live | 33     | A9635          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)      | 0.15-0.20mm (.006-.008")      | H233b axle, will not suit vehicles with oem locker                                                           | A9635-10TT         |
|                         |           |       |      |        | A13583         | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)      | 0.15-0.20mm (.006-.008")      | Replacement for oem locking differential                                                                     | A13583-10TT        |
|                         |           |       |      | 34     | A13281         |                   | 212Nm (156ftlb)                                     | 88Nm (55ftlb)      | 0.15-0.20mm (.006-.008")      | Suits h260 housing does not suit thrust block centre                                                         |                    |
|                         |           |       |      | 37     | A13092         |                   | 212Nm (156ftlb)                                     | 88Nm (55ftlb)      | 0.15-0.20mm (.006-.008")      |                                                                                                              |                    |
| Y62                     | 2010-     | FRONT | Ind. | 34     | A12539         |                   | 203Nm (150ftlb)                                     | 135Nm (100ftlb)    | 0.15-0.20mm (.006-.008")      | Confirm spline count                                                                                         |                    |
| NAVARA                  |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
| D21 - D22               | 1986-2016 | FRONT | Ind. | 27     | A11250         | TTEL15            | 69-78Nm (51-58ftlb)                                 |                    | 0.10-0.15mm (.004-.006")      | Housing & pinion may require modification                                                                    | A11250-15TT        |
|                         |           | REAR  | Live | 31     | A11257         | TTEL16            |                                                     |                    |                               | Ratio 4.11 & Up wheel bearing pre load must be checked post fittment                                         | A11257-16TT        |
|                         |           |       |      |        | A13620         | TTEL16            |                                                     |                    |                               | Ratio 3.9 & Down wheel bearing pre load must be checked post fittment                                        | A13620-16TT        |
|                         |           |       |      |        | A11825         | TTEL16            |                                                     |                    |                               | Ratio 4.25 & Up suits h233b housings made to order                                                           | A11825-16TT        |
| D40                     | 2005-2016 | FRONT | Ind. | 27     | A11120         | TTEL20            | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)      | 93Nm 0.10-0.15mm (.004-.006") | Ratio 3.69 & Up crown wheel must be fitted prior to electromagnet                                            | A11120-20TT        |
|                         |           |       |      |        | A11525         |                   | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)      | 93Nm 0.10-0.15mm (.004-.006") | Ratio 3.54 & Down crown wheel must be fitted prior to electromagnet                                          | A11525-20TT        |
|                         |           | REAR  | Live | 32     | A11119         | TTEL21            |                                                     |                    |                               | Suits 12-bolt crown wheel (thai built. Vin number start with mnt)                                            | A11119-21TT        |
|                         |           |       |      |        | A11568         |                   |                                                     |                    |                               | Suits 10-bolt crown wheel (spanish built vin start with vsk)                                                 | A11568-21TT        |
| D23 NP300               | 2014-2019 | FRONT | Ind. | 30     | A13120         | TTEL20            | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)      | 93Nm 0.10-0.15mm (.004-.006") | Ratio 3.54 & Down                                                                                            | A13120-20TT        |
|                         |           |       |      |        | A13684         |                   | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)      | 93Nm 0.10-0.15mm (.004-.006") | Ratio 3.69 & Up                                                                                              | A13684-20TT        |
|                         |           | REAR  | Live | 34     | A14799         | TTEL27            |                                                     |                    |                               | Ratio 3.69 & Up does not suit vehicles with oem locking differential                                         | A14799-27TT        |
| FRONTIER                |           |       |      |        |                |                   |                                                     |                    |                               |                                                                                                              |                    |
| D40                     | 2005-2016 | FRONT | Ind. | 27     | A11120         | TTEL20            | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)      | 93Nm 0.10-0.15mm (.004-.006") | Ratio 3.69 & Up crown wheel must be fitted prior to electromagnet                                            | A11120-20TT        |

# TERRAIN TAMER E-LOCKER FITTING GUIDE – 2024.

| VEHICLE MAKE & MODEL       | YEAR         | F/R   | SUSP | SPLINE | ELOCKER PART # | BEARING KIT PART# | CROWN WHEEL TORQUE                                  | BEARING CAP TORQUE                    | BACK LASH                          | COMMENTS                                                                                                                                                                           | TT DIFF LOCKER KIT |
|----------------------------|--------------|-------|------|--------|----------------|-------------------|-----------------------------------------------------|---------------------------------------|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
|                            |              |       |      |        | A11525         |                   | 59Nm (43ftlb) then turn an additional 34-39 degrees | 93Nm (69ftlb)                         | 93Nm 0.10-0.15mm (.004-.006")      | Ratio 3.54 & Down crown wheel must be fitted prior to electromagnet                                                                                                                | A11525-20TT        |
|                            |              | REAR  | Live | 32     | A11119         | TTEL21            | 198Nm (146ftlb)                                     | 108Nm (80ftlb)                        | .08-.013mm (.003-.005")            | Suits 12-bolt crown wheel (thai built. Vin number start with mnt)                                                                                                                  | A11119-21TT        |
|                            |              |       |      |        | A11568         |                   | 198Nm (146ftlb)                                     | 108Nm (80ftlb)                        | .08-.013mm (.003-.005")            | Crown wheel (spanish built vin start with vsk)                                                                                                                                     | A11568-21TT        |
| PATHFINDER                 |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| R50                        | 1995-2005    | FRONT | Ind. | 27     | A11250         | TTEL15            | 69-78Nm (51-58ftlb)                                 |                                       | 0.010-0.15mm (.004-.006")          | Light grinding will be required on the housing to clear elocker. Ensure there is clearance between pinion head and elocker body. Pinion head can be shaved down slightly to clear. | A11250-15TT        |
|                            |              | REAR  | Live | 33     | A9635          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)                         | 0.15-0.20mm (.006-.008")           | Ttel10 will be required to suit 50mm bearing journal on elocker will not suit vehicles with rear drum brakes                                                                       | A9635-10TT         |
| R51                        | 2005-2014    | FRONT | Ind. | 27     | A11120         | TTEL20            | 59Nm (43ftlb) then turn an additional 34-39 degrees | 93Nm (69ftlb)                         | 93Nm (0.10-0.15mm (.004-.006")     | Ratio 3.69 & Up crown wheel must be fitted prior to electromagnet                                                                                                                  | A11120-20TT        |
|                            |              |       |      |        | A11525         |                   | 59Nm (43ftlb) then turn an additional 34-39 degrees | 93Nm (69ftlb)                         | 93Nm (0.10-0.15mm (.004-.006")     | Ratio 3.54 & Down crown wheel must be fitted prior to electromagnet                                                                                                                | A11525-20TT        |
|                            |              | REAR  | Live | 33     | A12352         |                   |                                                     |                                       |                                    | Ratio 3.54 & Up                                                                                                                                                                    |                    |
|                            |              |       |      |        | A13238         |                   |                                                     |                                       |                                    | Ratio 3.36 & Down                                                                                                                                                                  |                    |
| TERRANO 2                  |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| R20                        | 1993-2006    | REAR  | Live | 31     | A9684          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)                         | 0.15-0.20mm (.006-.008")           | P/n# ttel10 will be required to suit 50mm bearing journal up-grade                                                                                                                 | A9684-10TT         |
|                            |              |       |      | 33     | A9635          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)                         | 0.15-0.20mm (.006-.008")           | P/n# ttel10 will be required to suit 50mm bearing journal up-grade does not suit models with rear drum brakes                                                                      | A9635-10TT         |
| FIAT                       |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| FULLBACK                   | 2016 -       | FRONT | Ind. | 28     | A11425         | TTEL33            | 85Nm (63ftlb)                                       | 60Nm (44ftlb)                         | 0.13-0.18mm (.005-.007")           | Will not suit 7.25" Crown wheel                                                                                                                                                    | A11425-33TT        |
|                            |              | REAR  | Live | 31     | A11428         | TTEL19            | 152Nm (112ftlb)                                     | 60Nm (44ftlb)                         | 0.13-0.18mm (.005-.007")           | 9.5" Crown wheel                                                                                                                                                                   | A11428-19TT        |
| FORD                       |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| EVEREST                    |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| UA                         | 2015-2018    | FRONT | Ind. | 29     | A11757         | TTEL24            | 135Nm (100ftlb)                                     |                                       | 0.35-0.45mm (.013-.017) off Pinion | Bearing journal sizes differ left to right (50.05/45.32)                                                                                                                           | A11757-24TT        |
| UA 2                       | 2018-        | FRONT | Ind. |        | A14408         | TTEL24            | 135Nm (100ftlb)                                     |                                       | 0.35-0.45mm (.013-.017) off Pinion | As above . Housing may require grinding to electro. Magnet seat                                                                                                                    | A14408-24TT        |
| RANGER                     |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| PJ & PK                    | 2006-2011    | FRONT | Ind. | 30     | A11474         | TTEL23            | 68-83Nm (51-62ftlb)                                 | 73-107Nm (84-79ftlb)                  | 0.09-0.11mm (.0035-.0043")         |                                                                                                                                                                                    | A11474-23TT        |
|                            |              | REAR  | Live | 32     | A11471         | TTEL22            | 95Nm (70ftlb)                                       | 81Nm (60ftlb)                         | 0.15-0.25mm (.006-.010")           |                                                                                                                                                                                    | A11471-22TT        |
| PX & PX2 (T6)              | 2011-7/2018  | FRONT | Ind. | 29     | A11757         | TTEL24            | 135Nm (100ftlb)                                     |                                       | 0.35-0.45mm (.013-.017) off Pinion | Bearing journal sizes differ left to right (50.05/45.32)                                                                                                                           | A11757-24TT        |
| PX3 P703 & RAPTOR          | 8/2018-      | FRONT | Ind. | 29     | A14408         | TTEL24            | 135Nm (100ftlb)                                     |                                       | 0.35-0.45mm (.013-.017) off Pinion | Suits px3 raptor. Bearing journal sizes differ, housing may require grinding.                                                                                                      | A14408-24TT        |
| PX & PX2 (T6) PX3 P703     | 2011-Current | Rear  | Live | 32     | A12608         | TTEL28            | 150Nm (110ftlb)                                     | 75Nm (55ftlb)                         | 0.15-0.25mm (.006-.010")           | Does not suit vehicles with oem locking differential                                                                                                                               | A12608-28TT        |
| MAVERICK                   | 1988-1997    | FRONT | Live | 31     | A9684          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)                         | 0.15-0.20mm (.006-.008")           | P/n# ttel10 will be required to suit 50mm bearing journal up-grade.                                                                                                                | A9684-10TT         |
|                            |              | REAR  | Live | 33     | A9635          | TTEL10            | 142Nm (105ftlb)                                     | 99Nm (73ftlb)                         | 0.15-0.20mm (.006-.008")           | Does not suit models with rear drum brakes.                                                                                                                                        | A9635-10TT         |
| ISUZU                      |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| DMAX & MU-X                | 2008-2019    | FRONT | Ind. | 17     | A11556         | TTEL11            | 107Nm (79ftlb)                                      | 98Nm (72ftlb)                         | 0.15-0.20mm (.006-.008")           |                                                                                                                                                                                    | A11556-11TT        |
|                            |              | REAR  | Live | 26     | A11559         | TTEL18            | 108Nm (80ftlb)                                      | 108Nm (80ftlb)                        | 0.15-0.20mm (.006-.008")           | Does suit vehicles with oem diff lock, due to isuzu casting differences this may require a different size shim to set the pre-load.                                                | A11559-18TT        |
|                            | 2020-        | FRONT | IFS  | 29     | A15305         | TTEL11            |                                                     |                                       |                                    |                                                                                                                                                                                    | A15305-11TT        |
| MU-X                       | 2014-2018    | FRONT | Ind. | 17     | A11556         | TTEL11            | 107Nm (79ftlb)                                      | 98Nm (72ftlb)                         | 0.15-0.20mm (.006-.008")           |                                                                                                                                                                                    | A11556-11TT        |
|                            |              | REAR  | Live | 26     | A11559         | TTEL18            | 108Nm (80ftlb)                                      | 108Nm (80ftlb)                        | 0.15-0.20mm (.006-.008")           | Due to isuzu casting differences this may require a different size shim to set the pre-load.                                                                                       | A11559-18TT        |
| FASTER & RODEO             | 1988-2007    | FRONT | Ind. | 17     | A11556         | TTEL11            |                                                     |                                       |                                    | Does not suit some rodeo's between 12/96 & 5/98 due to a different 3rd member and carrier. To get it to fit you can swap member out for an earlier one.                            | A11556-11TT        |
|                            |              | REAR  | Live | 26     | A11559         | TTEL18            |                                                     |                                       |                                    | Due to isuzu casting differences this may require a different size shim to set the pre-load.                                                                                       | A11559-18TT        |
|                            |              |       |      |        | A12924         |                   |                                                     |                                       |                                    | Suits vehicles with thrust block centre                                                                                                                                            |                    |
| HOLDEN                     |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| COLORADO                   |              |       |      |        |                |                   |                                                     |                                       |                                    |                                                                                                                                                                                    |                    |
| RC                         | 2008-2011    | FRONT | Ind. | 17     | A11556         | TTEL11            | 107Nm (79ftlb)                                      | 98Nm (72ftlb)                         | 0.15-0.20mm (.006-.008")           |                                                                                                                                                                                    | A11556-11TT        |
|                            |              | REAR  | Live | 26     | A11559         | TTEL18            | 108Nm (80ftlb)                                      | 108Nm (80ftlb)                        | 0.15-0.20mm (.006-.008")           | Due to isuzu casting differences this may require a different size shim to set the pre-load.                                                                                       | A11559-18TT        |
| RG/COLORADO7 & TRAILBLAZER | 2012-2020    | FRONT | Ind. | 28     | A11887         | TTEL25            | 120Nm (89ftlb)                                      | 63Nm (46ftlb) Alum 75Nm (55ftlb) Cast |                                    | Pre-load shim & baffle modification see instructions, Im102949 cone & Im102910 cup required.                                                                                       | A11887-25TT        |
|                            |              | REAR  | Live | 30     | A12086         | TTEL29            | 108Nm (80ftlb)                                      | 108Nm (80ftlb)                        | 0.15-0.20mm (.006-.008")           | Requires oem bearing does suit non thrust block model                                                                                                                              | A12086-29TT        |

## TERRAIN TAMER E-LOCKER FITTING GUIDE – 2024.

| VEHICLE MAKE & MODEL    | YEAR        | F/R   | SUSP | SPLINE | ELOCKER PART # | BEARING KIT PART# | CROWN WHEEL TORQUE                                  | BEARING CAP TORQUE   | BACK LASH                          | COMMENTS                                                                                                                                                   | TT DIFF LOCKER KIT |
|-------------------------|-------------|-------|------|--------|----------------|-------------------|-----------------------------------------------------|----------------------|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| RODEO                   |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| RA, RA7                 | 1988-2007   | FRONT | Ind. | 17     | A11556         | TTEL11            | 107Nm (79ftlb)                                      | 98Nm (72ftlb)        | 0.15-0.20mm (.006-.008")           | Does not suit some rodeo's between 12/96 & 5/98 due to a different 3rd member and carrier. To get it to fit you can swap member out for an earlier one.    | A11556-11TT        |
|                         |             | REAR  | Live | 26     | A11559         | TTEL18            | 108Nm (80ftlb)                                      | 108Nm (80ftlb)       | 0.15-0.20mm (.006-.008")           | Due to isuzu casting differences this may require a different size shim to set the pre-load.Does not suit models 88-02 with thrust block centre            | A11559-18TT        |
|                         |             |       |      |        | A12924         |                   | 108Nm (80ftlb)                                      | 108Nm (80ftlb)       | 0.15-0.20mm (.006-.008")           | Suits vehicles with thrust block centre 1993-                                                                                                              |                    |
| JACKAROO                |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| JACKAROO/UBS            | 1988-2002   | FRONT | Ind. | 17     | A11556         | TTEL11            | 107Nm (79ftlb)                                      | 98Nm (72ftlb)        | 0.15-0.20mm (.006-.008")           | Does not suit some jackaroo's between 12/96 & 5/98 due to a different 3rd member and carrier. To get it to fit you can swap member out for an earlier one. | A11556-11TT        |
|                         |             | REAR  | Live | 23     | A13444         |                   |                                                     |                      |                                    | Suits vehicles with factory lsd                                                                                                                            |                    |
|                         |             |       | Live | 26     | A11559         | TTEL18            | 108Nm (80ftlb)                                      | 108Nm (80ftlb)       | 0.15-0.20mm (.006-.008")           | Due to holden casting differences this may require a different size shim to set the pre-load.                                                              | A11559-18TT        |
| MAZDA                   |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| BT-50 UN                | 2006-2011   | FRONT | Ind. | 30     | A11474         | TTEL23            | 68-83Nm (51-62ftlb)                                 | 73-107Nm (84-79ftlb) | 0.09-0.11mm (.0035-.0043")         |                                                                                                                                                            | A11474-23TT        |
|                         |             | REAR  | Live | 32     | A11471         | TTEL22            | 95Nm (70ftlb)                                       | 81Nm (60ftlb)        | 0.15-0.25mm (.006-.010")           |                                                                                                                                                            | A11471-22TT        |
| BT-50 UP UR             | 2011-8/2018 | FRONT | Ind. | 29     | A11757         | TTEL24            | 135Nm (100ftlb)                                     |                      | 0.35-0.45mm (.013-.017) off Pinion | Bearings can be 2 different sizes so will need to checked upon install                                                                                     | A11757-24TT        |
|                         | 2011-9/2020 | REAR  | Live | 32     | A12608         | TTEL28            | 150Nm (110ftlb)                                     | 75Nm (55ftlb)        | 0.15-0.25mm (.006-.010")           | Does not suit vehicles with oem locking differential                                                                                                       | A12608-28TT        |
| BT-50 UR                | 2018 -2020  | FRONT | Ind. | 29     | A14408         | TTEL24            | 135Nm (100ftlb)                                     |                      | 0.35-0.45mm (.013-.017) off Pinion | Confirm build date suits ur facelift september 2018 onwards. Housing may require grinding.                                                                 | A14408-24TT        |
| BT-50 TF                | 6/2020-     | FRONT | Ind. | 29     | A15305         | TTEL11            |                                                     |                      |                                    | Tf model facelift june 2020 onwards                                                                                                                        | A15305-11TT        |
| MERCEDES                |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| X CLASS X220D X250D     | 2017-2020   | FRONT | Ind. | 30     | A13120         | TTEL20            | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)        | 93Nm 0.10-0.15mm (.004-.006")      | Ratio 3.54 & Down ratio needs to be confimed before ordering                                                                                               | A13120-20TT        |
|                         |             |       |      |        | A13684         |                   | 59Nm (43ftlb) then turn an additional 34-39 degress | 93Nm (69ftlb)        | 93Nm 0.10-0.15mm (.004-.006")      | Ratio 3.69 & Up ratio needs to be confirmed before ordering                                                                                                | A13684-20TT        |
| PAJERO                  |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| ND - NL                 | 1987-2000   | FRONT | Ind. | 28     | A11425         | TTEL33            | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Front: will not suit 7.25" Crown wheel                                                                                                                     | A11425-33TT        |
|                         |             | REAR  | Live | 31     | A11428         | TTEL19            | 152Nm (112ftlb)                                     | 78Nm (58ftlb)        | 0.13-0.18mm (.005-.007")           | 9.5" Crown wheel 3.5 V6 & 2.8td, bearing inner lm603049, outer lm603014                                                                                    | A11428-19TT        |
|                         |             | REAR  |      | 28     | A11970         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | 9.0" Crown wheel will not suit 3.5 V6 or 2.8td                                                                                                             |                    |
|                         |             | REAR  |      |        | A13105         |                   | 152Nm (112ftlb)                                     | 78Nm (58ftlb)        | 0.13-0.18mm (.005-.007")           | 8.0" Crown wheel                                                                                                                                           |                    |
| NM - NX                 | 2000-2018   | FRONT | Ind. | 28     | A11425         | TTEL33            | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Front: will not suit 7.25"Crown wheel                                                                                                                      | A11425-33TT        |
|                         |             | REAR  | Ind. | 33     | A12425         |                   | 152Nm (112ftlb)                                     | 78Nm (58ftlb)        | 0.13-0.18mm (.005-.007")           | 9.5" Crown wheel                                                                                                                                           |                    |
| TRITON                  |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| ME - MK                 | 1998-2002   | FRONT | Ind. | 28     | A11425         | TTEL33            | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Will not suit 7.25 Crown wheel                                                                                                                             | A11425-33TT        |
|                         |             | REAR  | Live | 28     | A11970         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits 9" crown wheel non thrust block centre                                                                                                               |                    |
|                         |             |       |      |        | A13905         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits thrust block variant rear                                                                                                                            |                    |
| MK-MR                   | 2002-2019   | Front | Ind. | 28     | A11425         | TTEL33            | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Will not suit 7.25 Crown wheel                                                                                                                             | A11425-33TT        |
|                         |             | Rear  | Live | 31     | A11428         | TTEL19            | 152Nm (112ftlb)                                     | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits 9.5" Crown wheel                                                                                                                                     | A11428-19TT        |
| MR                      | 2020 -      | Rear  | Live | 28     | A11428         | TTEL19            | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits 9.5" Crown wheel will not suit factory diff lock                                                                                                     | A11428-19TT        |
|                         |             | Rear  | Live | 31     | A15085         |                   | 152Nm (112ftlb)                                     | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits factory locker replacement                                                                                                                           |                    |
| CHALLENGER/PAJERO SPORT |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| PA - QE                 | 1988-2016   | FRONT | Ind. | 28     | A11425         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Will not suit 7.25" Crown wheel                                                                                                                            |                    |
|                         |             | REAR  | Live | 31     | A11428         | TTEL19            | 152Nm (112ftlb)                                     | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits 9.5" Crown wheel                                                                                                                                     | A11428-19TT        |
|                         |             |       |      | 28     | A11970         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits 9.0" Crown wheel                                                                                                                                     |                    |
|                         |             |       |      |        | A13105         |                   | 152Nm (112ftlb)                                     | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Suits 8.0" Crown wheel                                                                                                                                     |                    |
| DELICA                  |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| L300                    | 1986-1994   | FRONT | Ind. | 28     | A11425         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Will not suit 7.25" Crown wheel                                                                                                                            |                    |
|                         |             | REAR  | Live |        | A13105         |                   | 152Nm (112ftlb)                                     | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | 8.0" Crown wheel                                                                                                                                           |                    |
| L400                    | 1994-2007   | FRONT | Ind. |        | A11425         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | Will not suit 7.25" Crown wheel                                                                                                                            |                    |
|                         |             | REAR  | Live |        | A11970         |                   | 85Nm (63ftlb)                                       | 60Nm (44ftlb)        | 0.13-0.18mm (.005-.007")           | 9.5" Crown wheel non thrust block centre bearing inner lm603049, outer lm603014                                                                            |                    |
| GREAT WALL              |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |
| V240                    | 2006-2016   | REAR  | Live | 30     | A12053         |                   |                                                     |                      |                                    | Built to order                                                                                                                                             |                    |
| JEEP                    |             |       |      |        |                |                   |                                                     |                      |                                    |                                                                                                                                                            |                    |

# TERRAIN TAMER E-LOCKER FITTING GUIDE – 2024.

| VEHICLE MAKE & MODEL      | YEAR      | F/R   | SUSP | SPLINE | ELOCKER PART # | BEARING KIT PART# | CROWN WHEEL TORQUE | BEARING CAP TORQUE | BACK LASH                | COMMENTS                                                                 | TT DIFF LOCKER KIT |
|---------------------------|-----------|-------|------|--------|----------------|-------------------|--------------------|--------------------|--------------------------|--------------------------------------------------------------------------|--------------------|
| GALDIATOR/GT              | 2020-     | FRONT | Live | 32     | A14989         |                   |                    |                    |                          | Dana 44 same differential front & rear                                   |                    |
|                           |           | REAR  | Live | 32     | A14989         |                   |                    |                    |                          | Dana 44 same differential front & rear                                   |                    |
| WRANGLER/TJ               | 1997-2006 | FRONT | Live | 27     | 63-19817-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.54 & Down ratio suits dana 30 housing 7.2" Crown wheel diameter        |                    |
|                           |           |       |      |        | 63-19818-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.73 & Up ratio suits dana 30 housing 7.2" Crown wheel diameter          |                    |
|                           |           | REAR  | Live | 27     | 63-19821-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.54 & Up ratio suits dana 35 housing c -clip 7.56" Crown wheel diameter |                    |
|                           |           |       |      | 30     | A19977         |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | Suits dana 44 housing 3.73 & Down ratio 8.5" Crown wheel diameter        |                    |
|                           |           |       |      |        | 63-19969-010   |                   |                    |                    |                          | Suits dana 44 housing 3.92 Up ratio 8.5" Crown wheel diameter            |                    |
| WRANGLER/JK               | 2006-2018 | FRONT | Live | 27     | 63-19817-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.54 & Down ratio suits dana 30 housing 7.2" Crown wheel diameter        |                    |
|                           |           |       |      |        | 63-19818-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.73 & Up ratio suits dana 30 housing 7.2" Crown wheel diameter          |                    |
|                           |           | REAR  | Live | 30     | A19977         |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | Suits dana 44 housing all ratios 8.5" Crown wheel diameter               |                    |
| WRANGLER/JL               | 2020-     | FRONT | Live | 27     | 63-19817-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.54 & Down ratio suits 7.2" Crown wheel                                 |                    |
|                           |           |       |      |        | 63-19818-020   |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | 3.73 & Up ratio suits 7.2" Crown wheel                                   |                    |
|                           |           | REAR  | Live | 29     | A15359         |                   |                    |                    |                          | M200 diffrential                                                         |                    |
| LDV                       |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| T60 PRO                   | 2017-     | REAR  | Live | 32     | A14816         |                   |                    |                    |                          |                                                                          |                    |
| LAND ROVER                |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| DISCOVERY                 |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| DISCOVERY 1 / DISCOVERY 2 | 1993-2004 | FRONT | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
|                           |           | REAR  |      |        | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
| DEFENDER                  |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| DEFENDER 110, 130, COUNTY | 1983-2014 | FRONT | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
|                           |           |       |      |        | A11870         |                   | 136Nm (43ftlb)     | 134Nm (99ftlb)     | 0.15-0.25mm (.006-.010") | Ratio 4.10 & Down suits salisbury 8ha housing.                           |                    |
|                           |           |       |      |        | A13201         |                   | 136Nm (43ftlb)     | 134Nm (99ftlb)     | 0.10-0.17mm (.004-.007") | Ratio 4.56 & Up suits salisbury 8ha housing                              |                    |
|                           |           | REAR  | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
|                           |           |       |      |        | A11870         |                   | 136Nm (43ftlb)     | 134Nm (99ftlb)     | 0.15-0.25mm (.006-.010") | Ratio 4.10 & Down suits salisbury 8ha housing.                           |                    |
|                           |           |       |      |        | A13201         |                   | 136Nm (43ftlb)     | 134Nm (99ftlb)     | 0.10-0.17mm (.004-.007") | Ratio 4.56 & Up suits salisbury 8ha housing                              |                    |
|                           |           |       |      |        | A11415         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Suits p38a housing                                                       |                    |
| DEFENDER 90               | 1983-2012 | FRONT | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
|                           |           | REAR  | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
| PERENTIE 6X6              | 1987-1993 | FRONT | Ind. | 24     | A13178         | TTEL25            | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       | A13178-25TT        |
|                           |           | REAR  | Live | 24     | A11870         |                   | 136Nm (43ftlb)     | 134Nm (99ftlb)     | 0.15-0.25mm (.006-.010") | Ratio 4.10 & Down suits salisbury 8ha housing.                           |                    |
|                           |           |       |      |        | A13201         |                   | 136Nm (43ftlb)     | 134Nm (99ftlb)     | 0.10-0.17mm (.004-.007") | 4.56 And up ratio suits salisbury 8ha housing.                           |                    |
| RANGE ROVER               |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| SERIES 1                  | 1970-1996 | FRONT | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
|                           |           | REAR  | Live | 24     | A11301         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Rover differential                                                       |                    |
| P38A                      | 1993-2016 | FRONT | Live | 24     | A11415         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Suits p38a housing                                                       |                    |
|                           |           | REAR  | Live | 24     | A11415         |                   | 58Nm (43ftlb)      | 90Nm (66ftlb)      | 0.10-0.17mm (.004-.007") | Suits p38a housing                                                       |                    |
| PORSCHE / VW              |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| CAYENNE 995 & 997         | 2003-2010 | FRONT | IFS  | 37     | A15117         |                   |                    |                    |                          | Oe bearings can be used. (Lm503349a & lm503310)                          |                    |
| TOUAREG                   | 2002-2010 | FRONT | IFS  | 37     | A15117         |                   |                    |                    |                          | Oe bearings can be used. (Lm503349a & lm503310)                          |                    |
| SSANGYONG                 |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| MUSSON/REXTON/ KORANDO    | 1996-2016 | REAR  | Live | 30     | A19977         |                   | 75Nm (55ftlb)      | 81Nm (60ftlb)      | 0.15-0.25mm (.006-.010") | Ratio 3.73 & Down suist dana 44 housing                                  |                    |
| SUZUKI                    |           |       |      |        |                |                   |                    |                    |                          |                                                                          |                    |
| GRAND VITARA              | 2005 -    | REAR  | Live |        | A13558         |                   |                    |                    |                          | Irs housing requires modifications, requires oe carrier bearings         |                    |

